## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	or trade mark:	Modern Living
-----------------	----------------	---------------

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271195

Type of light sour	Type	of li	ght	sourc	e:
--------------------	------	-------	-----	-------	----

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	LED Module			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product parameters				
Parameter	Value	Parameter	Value	

Froduct parameters				
Parameter		Value	Parameter	Value
General product parameters:				
	mption in on- 00 h), rounded st integer	18	Energy efficiency class	D
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	2 700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	18,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	2	Spectral power dis-	See image
sions without	Width	10	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	3 750	range 250 nm to 800 nm, at full-load	

Lucuto and uses	1			
parts and non-				
lighting con-				
trol parts, if				
any (millime-				
tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent	-	
		power (W)		
		Chromaticity coordi-	0,438	
		nates (x and y)	0,403	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	5	Survival factor	0,90	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,90	Colour consistency	5	
		in McAdam ellipses		
Claims that an LED light source	_(b)	If yes then replace-	-	
replaces a fluorescent light		ment claim (W)		
source without integrated bal-		, ,		
last of a particular wattage.				
	0.2	Stroboscopic offect	0.5	
Flicker metric (Pst LM)	0,2	Stroboscopic effect metric (SVM)	0,5	

(a)'-': not applicable; (b)'-': not applicable;

