Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: | Premium Living |
|--------------------------------|----------------|
|--------------------------------|----------------|

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271302

| _ | • | | |
|------|-----|--------|---------|
| Typa | Λt | liaht | source: |
| IVDE | VI. | IIKIIL | source. |

| High luminance light source: Anti-glare shield: | No No No Product parar | Envelope: Dimmable: meters | Yes |
|---|--|---------------------------------|----------|
| | No | | - Yes |
| High luminance light source: | | Envelope: | - |
| | No | Envelope: | - |
| Colour-tuneable light source: | | | T . |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Light source cap-type (or other electric interface) | LED Module | | |
| Lighting technology used: | LED | Non-directional or directional: | NDLS |

| | Troduct parameters | | | |
|---|---|---------------------------|--|--------------|
| Parameter | | Value | Parameter | Value |
| | | General product p | arameters: | |
| Energy consur mode (kWh/10 up to the neares | • • | 15 | Energy efficiency class | G |
| dicating if it refe a sphere (360º) | s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º) | 1 100 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 30006500 |
| On-mode pow pressed in W | ver (P _{on}), ex- | 15,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| (P _{net}) for CLS, 6 | andby power expressed in W the second dec- | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 81 |
| Outer dimen- | Height | 1 | Spectral power dis- | See image |
| sions without | Width | 200 | tribution in the | in last page |
| separate con- trol gear, light- ing control | Depth | 200 | range 250 nm to 800 nm, at full-load | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | |
|---|------|--|----------------|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,311 0,332 |
| Parameters for LED and OLED light sources: | | | |
| R9 colour rendering index value | 0 | Survival factor | 0,90 |
| the lumen maintenance factor | 0,96 | | |
| Parameters for LED and OLED mains light sources: | | | |
| displacement factor (cos φ1) | 0,80 | Colour consistency in McAdam ellipses | 6 |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replace- ment claim (W) | - |
| Flicker metric (Pst LM) | 0,1 | Stroboscopic effect metric (SVM) | 0,1 |

(a)'-': not applicable; (b)'-': not applicable;

