



#### High-performance odour removal

5000 ExtractionTech Plus ensures your kitchen air stays fresh and clean every time you cook. The high-performance motor thoroughly cleans the air and removes odours for a better cooking environment.

### Product Benefits & Features

#### ExtractionTech Plus: High-performance odour removal

ExtractionTech Plus keeps your kitchen smelling fresh and clean every time you cook. The high-performance motor thoroughly cleans the air and removes odours for a better cooking environment.



#### Spotlight the details with the Pure Illumination

Energy-efficient Pure Illumination provides full visibility while cooking. The LED lights illuminate the entire cooking surface, making it easy to see every detail of your meal preparation.



#### Reliable, easy-to-clean grease filter keeps kitchen fresh

Convenient, reliable grease filter ensures your kitchen stays fresh and hood performs at its best. Wash by hand or in dishwasher.



- Installation type: Island, width 90 cm
- Power settings in recirculation mode (high/low): 415 / 250 m³/h
- Push button controls with 3 speeds
- Number of speeds: 3
- LED spotlight: (Number of lamps: 4, Total lighting power: 11.7 Watt)
- Light Temperature, K
- Watt Volt
- Number of motors: 1
- Motor absorption: 210 W
- Grease filter type and number: Aluminium mesh, 3
- Carbon active filter ECFB01ST, PNC 902 986 573, 1;Included
- Exhaust air and recirculated air operation
- Maximum noise level (high/low): 61/46 dB(A)
- Suitable special accessories: exhaust air hose KPIPE150, 942 492 724

## Product Specification

Product Number Code	942 051 338	Recirculation High	290
EAN	7332543713950	Sound power max speed, dB(A)	68
EPREL Registration Code	363714	Sound power min speed, dB(A)	51
Annual Energy consumption, KWh/annum	101.3	Recirculation Max, m³/h-2ndGen	415
Energy Efficiency class	C	Recirculation Min, m³/h-2ndGen	250
Fluid dynamic efficiency class	D	Recirc. sound power max, dB(A)	73
Fluid dynamic efficiency index	15.3	Recirc. sound power min, dB(A)	62
Lighting efficiency class	A	Off mode power, W	0.01
Lighting efficiency index	38.1	Light temperature, K	3000
Grease filter efficiency class	C	Remote control	Not available
Grease filter efficiency index	75.1	Min dist.from cook.top electric, cm	50
Height, mm	730	Min dist.from cook.top gas, cm	65
Height max. external, mm	1150	Gross weight, kg	33.3
Width, mm	898	Net weight, kg	23.6
Depth, mm	598	Package height, mm	580
Air outlet, mm	150	Package width, mm	1010
Main colour	Stainless Steel	Package depth, mm	510
OdourClean Standard Carbon filter PNC	902 986 573	Weight (g) of Corrugated Cardboard	8600
Volt, V	230-240	Weight (g) of Paper/Carton	400
OdourClean Standard Carbon filter type	ECFB01ST	Weight (g) of Wood	800
Capacity max, m³/h	600	Weight (g) of Polyethylene (PE)	0
Capacity min, m³/h	295	Weight (g) of Polypropylene (PP)	0
		Weight (g) of Polystyrene (EPS/EPP)	0
		Weight (g) of PU Foam	0
		Weight (g) of Iron/Steel	0

