Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name o	or trade mark:	Modern Living
------------	--------	----------------	---------------

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271396-01

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

separate con-

trol gear, light-

control

ing

Depth

Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		LED Module		
(or other electric interface)				
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	Yes
		Product para	meters	
Parameter		Value	Parameter	Value
		General product	parameters:	
	nption in on- 00 h), rounded st integer	3	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P _{on}), ex- pressed in W		3,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	2	Spectral power dis-	See image
sions without	Width	120	tribution in the	in last page
			J 250 I. 222	

75

range 250 nm to 800

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,440			
		nates (x and y)	0,403			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	2	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

