Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name	or trad	e mark:	Bessagi Home
------------	------	---------	---------	--------------

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271235

Type	of	light	source:
-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		0	

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	LED module			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	Yes	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Yes	
Dundret neversetore				

Product parameters

Product parameters				
Parameter		Value	Parameter	Value
General product parameters:				
0,	nption in on- 00 h), rounded st integer	40	Energy efficiency class	Е
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		5 300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30006500
On-mode power (P _{on}), expressed in W		40,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	3	Spectral power dis-	See image
sions without	Width	4 080	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	10	range 250 nm to 800 nm, at full-load	

parts and non-			
lighting con-			
trol parts, if			
any (millime-			
' '			
tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent	-
		power (W)	
		Chromaticity coordi-	0,431
		nates (x and y)	0,397
Darameters for LED and OLED lie	ht courses	, , ,	
Parameters for LED and OLED lig	gnt sources:		
R9 colour rendering index value	4	Survival factor	0,90
the lumen maintenance factor	0,96		
Parameters for LED and OLED m	ains light sources:		
displacement factor (cos φ1)	0,90	Colour consistency	6
, , , ,	,	in McAdam ellipses	
Claims that an LED light source	_(b)	If yes then replace-	-
replaces a fluorescent light		ment claim (W)	
source without integrated bal-		(11)	
last of a particular wattage.			
Flicker metric (Pst LM)	0,1	Stroboscopic effect	0,1
		metric (SVM)	

(a)'-': not applicable; (b)'-': not applicable;

