Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or t	ade mark: N	Modern Living
----------------------	-------------	---------------

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271467-01

Type of light source	Type	of lig	ht so	ource:
----------------------	------	--------	-------	--------

Type of light source:					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED Module				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	Yes		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					
Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on-	36	Energy efficiency	E		

	Class	
4 100 in	Correlated cold	our 3 000
Sphere (360°)	temperature,	
	. =	4 100 in Correlated cold

a sphere (360º), in a wide cone	rounded to the near-	
(120º) or in a narrow cone (90º)	est 100 K, or the	
	range of correlat-	
	ed colour temper-	
	atures, rounded to	
	the nearest 100 K,	
	that can be set	

On-mode power (P _{on}), expressed in W	36,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,40
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val-	80

			ues that can be set	
Outer dimen-	Height	2	Spectral power dis-	See image
sions without	***************************************	2 450	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	5	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,440 0,403
Parameters for LED and OLED lig	ght sources:		
R9 colour rendering index value	0	Survival factor	1,00
the lumen maintenance factor	0,96		
Parameters for LED and OLED m	ains light sources:		
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)'-': not applicable; (b)'-': not applicable;

