Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	Bessagi Home
--------------------------------	--------------

Supplier's address: Importableilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271365-02

_	•			
Type	Λt	liaht	COLL	rca.
IVDE	VI.	HEIIL	SOU	LC.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	LED Module		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
Product parameters			
Parameter	Value	Parameter	Value

Product parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
0,	nption in on- 00 h), rounded st integer	12	Energy efficiency class	F
dicating if it refe a sphere (360°)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	1 100 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pow pressed in W	ver (P _{on}), ex-	12,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,50
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	1 540	Spectral power dis-	See image
sions without	Width	12	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	2	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime-				
tre) Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,439 0,402	
Parameters for LED and OLED lig	Parameters for LED and OLED light sources:			
R9 colour rendering index value	0	Survival factor	0,90	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1	

(a)'-': not applicable; (b)'-': not applicable;

