## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name o	or trade mark:	Modern Living
------------	--------	----------------	---------------

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271524

Tvi	рe	of	lig	ht	SO	urce	:
. , ,		•	о		-		•

Lighting technology used:	LED	Non-directional or	NDLS
Lighting technology used.	LED		NDL3
		directional:	
Light source cap-type	LED Module		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light	No
		source (CLS):	
Calarin trina abla liabt accina	NI-	, ,	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
	Product para	ameters	
Parameter	Value	Parameter	Value
	General product	narameters:	

Parameter		Value	Parameter	Value
General product parameters:				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		6	Energy efficiency class	G
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone errow cone (90º)	540 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000 or 4 500 or 6 500
On-mode power (P <sub>on</sub> ), expressed in W		6,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without separate control gear, lighting control	Height	2	Spectral power dis-	See image in last page
	Width	235	tribution in the	
	Depth	235	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,440	
		nates (x and y)	0,403	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	-2	Survival factor	1,00	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

