Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	or trade mark:	Modern Living
-----------------	----------------	---------------

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271439

I V DC OI IISIIL JOUI CC	Type	of lig	tht s	ource:
--------------------------	------	--------	-------	--------

7,1 8				
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	LED Module			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product parameters				
Parameter	Value	Parameter	Value	
General product parameters:				

Froduct parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consummode (kWh/10 up to the neares	00 h), rounded	24	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	2 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pow pressed in W	ver (P _{on}), ex-	24,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without separate control gear, lighting control	Height Width Depth	2 2 320 10	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,440 0,403
Parameters for LED and OLED lig	tht sources:		
R9 colour rendering index value	5	Survival factor	1,00
the lumen maintenance factor	0,95		
Parameters for LED and OLED m	ains light sources:		
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)'-': not applicable; (b)'-': not applicable;