Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name or trade mark:	Premium Living
------------	---------------------	----------------

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 81810404 - Leselicht

_	•			
Typa	Λt	liaht	sourc	Δ.
IVDE	OI.	IIGIIL	3 Uui C	c.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	LED Module		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
Draduct parameters			

Product parameters

Product parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consummode (kWh/10 up to the neares	00 h), rounded	5	Energy efficiency class	Е
dicating if it refe a sphere (360°)	s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º)	570 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P _{on}), expressed in W		5,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	81
Outer dimen-	Height	2	Spectral power dis-	See image
sions without	Width	90	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	90	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,440 0,400
Parameters for LED and OLED light sources:			
R9 colour rendering index value	1	Survival factor	0,90
the lumen maintenance factor	0,90		
Parameters for LED and OLED m	ains light sources:		
displacement factor (cos φ1)	0,97	Colour consistency in McAdam ellipses	4
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)'-': not applicable; (b)'-': not applicable;

